USSN: 10/699,586 Group Art Unit: 3739

Docket No.: 151P11200US01

AMENDMENTS TO THE CLAIMS

- (Currently Amended) An apparatus for making a hole of a first predetermined diameter in a dura of a patient for the insertion of a catheter having a second predetermined diameter, comprising:
 - a catheter having a lumen;
 - a stylet having a first end adapted for insertion in said lumen;
 said stylet having a second end formed with a tip having a diameter having a
 predetermined relationship with said first predetermined diameter; and
 means for applying an electrical current to said tip of said stylet to cauterize said dura.
- 2. (Canceled)
- 3. (Original) An apparatus as in claim I wherein said tip has a hemispherical shape.
- 4. (Original) An apparatus as in claim 3 wherein said hemispherical shape has a diameter and wherein said diameter of said hemispherical shape is approximately equal to said first predetermined diameter.
- (Original) An apparatus as in claim 3 wherein said hemispherical shape has a
 diameter and wherein said diameter of said hemispherical shape is approximately equal to
 said second predetermined diameter.
- (Original) An apparatus as in claim 1 wherein said first predetermined diameter is approximately equal to said second predetermined diameter.
- (Original) An apparatus as in claim 1 wherein said first predetermined diameter is smaller than said second predetermined diameter.

USSN: 10/699,586 Group Art Unit: 3739

Docket No.: 151P11200US01

- 8. (Original) An apparatus as in claim 7 wherein said first predetermined diameter is approximately fifteen percent (15%) percent smaller than said second diameter.
- 9. (Original) A method of making a hole of a first predetermined diameter in a dura of a patient having a cranium for the insertion of a catheter having a second predetermined diameter, comprising the steps of:

determining whether to create a burr hole in said cranium of said patient;

inserting a first end of said stylet with a tip having a diameter having a predetermined relationship with said first predetermined diameter into said burn hole of said cranium;

applying an electrical current to said stylet in order to cauterize said dura creating a hole in said dura approximately equal to said diameter of said tip; and

inserting a second end of said stylet into a lumen of a catheter with said second end of said stylet proximal to a distal end of said catheter.

- 10. (Original) A method as in claim 9 wherein said tip of said stylet has a hemispherical shape.
- 11. (Original) A method as in claim 10 wherein said hemispherical shape has a diameter and wherein said diameter of said hemispherical shape is approximately equal to said first predetermined diameter.
- 12. (Original) A method as in claim 10 wherein said hemispherical shape has a diameter and wherein said diameter of said hemispherical shape is approximately equal to said second predetermined diameter.
- 13. (Original) A method as in claim 9 wherein said first predetermined diameter is approximately equal to said second predetermined diameter.

USSN: 10/699,586 Group Art Unit: 3739

Docket No.: 151P11200US01

- 14. (Original) A method as in claim 9 wherein said first predetermined diameter is smaller than said second predetermined diameter.
- 15. (Original) A method as in claim 14 wherein said first predetermined diameter is approximately fifteen percent (15%) smaller than said second diameter.